



Cottrell – Fibre

Material Data Sheet

Item:

Cottrell Fibre- Electrical Insulating Paper

Description:

Cottrell Fibre electrical insulating papers are 100% Copaco Rag Stock papers further enhanced to provide excellent rigidity and low water absorption. Meets ASTM D710 and MIL-I-695.

Application:

Cottrell Fibre is available in continuous rolls, sheets, or in coils slit to your specifications. This grade is currently manufactured in thicknesses from .010" to .060".

Typical Test Values:

Thickness +/- 10%	Tear (g) MD	Tear (g) CD	Tensile (psi) MD	Tensile (psi) CD	Elongation % MD	Elongation % CD
.005"	140	155	14,000	7,000	3.6	10.0
.007"	215	220	12,900	8,000	3.1	9.0
.010"	275	350	15,685	9,100	7.3	9.8
.015"	490	490	13,000	10,000	4.5	9.0
.020"	650	820	16,250	9,100	8.0	11.0
.032	1650	1948	16,000	9,000	7.5	10.0

Moisture: <6%
 Water Absorption 24 hr <60%
 Dielectric: Greater than 250 volts per mil (420vpm typical)
 Methanol Extractables: 0.15 - 0.20%
 Density: 1.15 - 1.25
 PH 7.0

- These figures are typical values only and do not constitute a specification.
- Current specifications for all materials are always available on request.
- Cottrell Paper Company's continuous improvement efforts may lead to changes in the above data

Please call us toll free at 1-800-948-3559

Email : tom@cottrellpaper.com
 Website : www.cottrellpaper.com