



ROUNDIT®

PROTECTIVE CABLE WRAP



ROUNDIT® 2000

- Operating temperature from -70°C up to +125°C
- Self-wrapping design
- Excellent abrasion resistance
- UL recognized
- Nominal sizes available from 3/16" to 1-1/2"




ROUNDIT® 2000 FR

- Operating temperature from -50°C up to +125°C
- Self-wrapping design
- Flame-retardant
- Halogen free
- Highly flexible
- Nominal sizes available from 3/16" to 1-1/2"




ROUNDIT® 2000 - White

- Operating temperature from -70°C up to +125°C
- Self-wrapping design
- Aesthetic solution for visible applications
- Nominal sizes available from 5/16" to 1"




ROUNDIT® 2000 NX

- Operating temperature from -60°C up to +200°C
- Self-wrapping design
- Excellent abrasion resistance
- Halogen free
- Meets FAR Part 25
- Oil and water repellent
- Nominal sizes available from 3/16" to 1-1/2"



ROUNDIT® 2000-V0

- Operating temperature from -50°C up to +125°C
- Self-wrapping design
- Excellent abrasion resistance
- Flame resistant
- Halogen free
- Ideal for railway applications



ROUNDIT® 2000 TF (Teflon)

- Operating temperature from -70°C up to +200°C
- Self-wrapping design
- Highly flexible
- Meets FAR Part 25
- Halogen free
- Fray resistant
- Nominal sizes available from 1/8" to 1"

www.federal-mogul.com/spg • 1.800.926.2472