



**The Competitive
Edge To Better Glass
Bands**

Fibertek Res-I-Straint is an important component of the complete Fibertek Banding System. It assures your glass band of being the strongest, most secure and most accurate possible. Res-I-Straint Tadpole Edge Restraining Tape is a resin impregnated and B-Stage edging tape used in conjunction with glass banding tape to provide a more uniform glass band. It can also be used as a means of band



stress relief when banding a wide area by using a third or intermediate restraint in the center of the glass band. Res-I-Straint is placed upon the armature prior to the banding tape application and the sewn-in bead

forms the outer edges of the glass band. Hence, the diameter of the bead is proportionate to the thickness of the band.

Why Res-I-Straint?

Res-I-Straint is resin impregnated to provide a homogeneous band with the glass banding tape during the cure cycle. Unlike lesser grade competitive products, Res-I-Straint is made using glass cloth which is a full 7 mil. thickness in the base material. It is available in numerous bead diameters to cover the requirements of standard band thicknesses. Since this is a B-Stage product it is recommended that the same refrigerated storage practices for banding tape be followed for Res-I-Straint. Unlike competitive products, Res-I-Straint is supplied in heat sealed poly bags to insure freshness and prolong shelf life.



P.O. Box 4000 • 305 Beasley Drive
Franklin, Tennessee 37065

Phone 615•794•1400
Fax 615•790•8289

STOCK RES-I-STRAINT SIZES

PART NO.	BEAD DIA.	TAPE WIDTH	CORE LENGTH	CORE I.D.	YARDAGE
FRS321	3/32"	1"	10"	3"	100 YARDS
FRS521	5/32"	1"	10"	3"	100 YARDS
FRS361.5	3/16"	1 1/2"	10"	3"	100 YARDS
FRS363	3/16"	3"	10"	3"	100 YARDS
FRS142	1/4"	2"	10"	3"	100 YARDS

NOTE: Custom widths and bead diameters available on special order. Consult factory on specifications.

