



Soft & Flexible With Unyielding Strength

Fibertek B-Stage Surge Rope is preferred by industry leaders not only because of its superior performance qualities, but is the choice of those who work with it everyday because of its application flexibility, and equally important soft polyester finish that protects their hands from glass fibers and raw resins. Fibertek B-Stage Surge Rope provides greater protection for

your work and your workers.

Fibertek Surge Rope is constructed using a core of glass yarns which have been impregnated with a thermosetting modified polyester resin system rated at Class H Plus/220° C. The B-Stage core is overbraided with a spun polyester fiber encapsulating the core. It is designed for surge ring and other structural applications requiring a rigid insulating and high mechanical strength material.

Why Fibertek B-Stage Surge Rope?

The Fibertek B-Stage Surge Rope incorporates a 35% resin content of 220° C modified polyester resin. The polyester braid provides a dry, user friendly jacket which eliminates the need to directly handle glass fibers during installation. The braid provides for a more flexible product which enables the user to tie tighter knots and eliminates the need for additional protection around the coils.



P.O. Box 4000 • 305 Beasley Drive
Franklin, Tennessee 37065

Phone 615•794•1400
Fax 615•790•8289

STOCK SURGE ROPE SIZES

PART NO.	DIAMETER	LENGTH	RESIN CONTENT	RESIN THERMAL CLASS
SRR 14	1/4"	100 Ft.	35%	220°C
SRR 38	3/8"	100 Ft.	35%	220°C
SRR 716	7/16"	100 Ft.	35%	220°C
SRR 12	1/2"	50 Ft.	35%	220°C
SRR 58	5/8"	50 Ft.	35%	220°C
SRR 34	3/4"	50 Ft.	35%	220°C
SRR 78	7/8"	50 Ft.	35%	220°C

