



JENSEN GLOBAL

Dispensing Solutions

Tel 805-965-3668

Fax 805-456-2039







JGD300S Dispensing Shot Meter

Jensen Global's JGD300S compact benchtop dispenser allows for reproducible deposits of a wide range of thin or viscous materials such as solder pastes and masks, adhesives, epoxies, RTV's and silicones, cyanoacrylates, paints and inks. It is excellent for use with pre-filled syringes of materials, or when loading empty syringes.

The analog timer enables the production of a controlled deposit amount. Vacuum pull back will assist with a cleaner deposit when materials have tendencies to string.



Features and Accessories Included:

-  Timer .01 to 30 sec
-  Vacuum Pull Back
-  Power supply 100-240V
-  Durable yet lightweight foot pedal
-  5/32" and 1/4" unique tubing adapter fittings
-  Needle samples

Specifications

Dimensions W x H x D

4.50 x 6.25 x 7.75"

11.4 x 15.8 x 19.9 cm

Weight

2.4 lbs (1.09 kg)

Power Supply

Input 100-240VAC

Output 24VDC 1A

Timer Range

00.01 to 30 seconds

Air Input

35-100 psi (2.4-6.9 bar)

Air Output

1-100 psi (0.1-6.9 bar)

Options

Syringe Stand

JGD816

Needle Kit

JG120NK

Adapters

JG1CCUSA-C

JG3A-XC6

JG5A-XC6

JG10A-XC6

JG30A-XC6

JG50A-XC6



Syringe Kit

JG120NS

Syringes

JG3A-50

JG5A-40

JG10A-40

JG30A-20

JG50A-10



With Vacuum Pick-Up Wand

JGD300SMT

SMT re-work dispensing system



www.jensenglobal.com

info@jensenglobal.com