

# LOCTITE®



## Revolutionizing Threadlocking... One threaded fastener at a time.

- ▶ The First Threadlocker in Tape Form!
- ▶ No Mess, No Waste
- ▶ Same Reliability & Performance as Loctite® Removable Grade Threadlocking Liquids
- ▶ A **MUST** for Every Toolbox!

Loctite® QuickTape™ 249™  
Threadlocker Tape



Henkel



Introducing Henkel's newest innovation – Loctite® QuickTape™ 249™. The first tape form of threadlocking to embody the same reliable performance you've come to expect from Loctite® liquids and sticks. It's neat, clean and couldn't be easier to apply. Just peel the tape from the spool, wrap the tape around the bolt, and tear. Then toss it into your toolbox for the next time.

## Join The Revolution...

### Loctite® QuickTape™ 249™ Threadlocker Tape

Loctite® QuickTape™ adds a new dimension to the Loctite® line of threadlockers. Due to its unique capabilities, Loctite® QuickTape™ 249™ is the perfect complement to Henkel's expansive line of liquid threadlocking products.

- ▶ **Easy to use**
- ▶ **Familiar application method**
- ▶ **Toolbox/Tool belt/Pocket friendly**
- ▶ **No mess**
- ▶ **Can be pre-applied for future assembly**



Step 1: **PEEL**



Step 2: **WRAP\***



Step 3: **TEAR**



Step 4: **ASSEMBLE**



\*Number of wraps required is dependent upon the size of the fastener. For a typical 3/8" bolt, 2 to 3 wraps are sufficient. Please refer to the Loctite® Data Sheet for additional information.

Loctite® QuickTape™ 249™ Threadlocking Adhesive						
Loctite® Part No.	Package Size	Color	Typical Use	Cure Time (Fixture/Full Cure)	**Torque, In-lbs. Break/Prevail	Temperature Range
1372603	260" Roll	Blue	Medium strength, general-purpose threadlocker. Removable with hand tools.	30 min./24 hours	74/47	-65°F to 300°F (-54°C to 150°C)

\*\*Typical value on 3/8" x 16 steel nuts and bolts, cured for 24 hours at 72°F (22°C).

Go to [www.useloctite.com](http://www.useloctite.com)

to find out more and see a video demonstration!!



**Henkel Corporation**  
**Engineering Adhesives**  
[www.henkelna.com/mrnew](http://www.henkelna.com/mrnew)

**U.S.A.**  
**Henkel Corporation**  
 Engineering Adhesives  
 One Henkel Way  
 Rocky Hill, Connecticut 06067  
 Tel: 1.800.LOCTITE (562.8483)  
 Tel: 860.571.5100  
 Fax: 860.571.5465

**Canada**  
**Henkel Canada Corporation**  
 Engineering Adhesives  
 2225 Meadowpine Blvd.  
 Mississauga, Ontario L5N 7P2  
 Tel: 1.800.263.5043 (within Canada)  
 Tel: 905.814.6511  
 Fax: 905.814.5391

Except as otherwise noted, all marks used in LT-5709 are trademarks and/or registered trademarks of Henkel and/or its affiliates in the U.S. and elsewhere. © = registered in the U.S. Patent and Trademark Office. © Henkel Corporation, 2010. All rights reserved. 6110/LT-5709 (2/10)