

PROHEAT[®] HEAT GUNS

**Compact • Light Weight • Easy-to-Use
Professional Quality Heat Guns**



MASTER[®]
APPLIANCE
Designers and Manufacturers of Heat Tools for Industry

PROHEAT® VARITEMP® HEAT GUN

- Dial-in temperature settings with easy access, top mounted temperature control
- Variable temperatures 54°C to 449°C
- Patented electronic closed-loop temperature control system maintains constant temperature and protects unit from overheating when using specialty attachments
- 230V, 50/60 Hz, 6.2A, 1410W maximum

- Compact, light weight, easy-to-use design
- Durable enclosed ceramic heating element
- Heavy duty Lexan® plastic housing has built-in stand and hanging loop for hands-free operation
- Balanced design prevents operator fatigue and improves accuracy in use
- Permanent magnet DC motor delivers powerful airflow at 425 l/m
- Industrial quality, 3-wire grounded cordset and hand/switch guard for safety
- Made in the USA, 12 month warranty
- Multiple attachments & bench stand available separately



Easy access
heat control

PH-2200



PH-2200

Well balanced design



PH-2200-1

Terminate specialty
connectors



PH-2200K

Kit includes heat gun, shrink, spreader
pinpoint, reducer and specialty
connector attachments
with storage case

ORDERING INFORMATION

Model No.	Description
PH-2200	Proheat Varitemp Heat Gun 230V, 50/60Hz, 6.2A
PH-2200-1	Proheat Varitemp Shrink System includes heat gun, stand and attachment (35292)
PH-2200K	Proheat Varitemp Kit includes heat gun, attachments (35309) and storage case

TECHNICAL SPECIFICATIONS: PH-2200, PH-2200-1, PH-2200K

Voltage: 230V, 50/60Hz, 6.2A

Output: 1410W maximum

Temperature: Variable 54°C to 449°C

Airflow Volume: 425 l/min.

Motor: Permanent magnet

Nozzle Opening: 22.1cm diameter

Cordset: 1.82m 3-wire grounded

Dimensions: 20.8cm L x 7.6cm W x 25.5cm H

Net Weight Gun Only: 0.737kg

Shipping Weight PH-2200: 1.36kg

Shipping Weight PH-2200-1: 1.5kg

Shipping Weight PH-2200K: 3.18kg

U.S. Patent No's. 5.349.161, 334.876

PROHEAT[®] HEAT GUN

- Dual temperatures 221°C or 449°C
- 3-position rocker switch
- 230V, 50/60 Hz, 6.2A, 1410W maximum

- Compact, light weight, easy-to-use design
- Durable enclosed ceramic heating element
- Heavy duty Lexan[®] plastic housing has built-in stand and hanging loop for hands-free operation
- Balanced design prevents operator fatigue and improves accuracy in use
- Permanent magnet DC motor delivers powerful airflow at 425 l/m
- Industrial quality, 3-wire grounded cordset and hand/switch guard for safety
- Made in the USA, 12 month warranty
- Multiple attachments & bench stand available separately



PH-2100



PH-2100

Well balanced design



All Proheat Heat Guns have a built-in stand for hands-free use.



PH-2100K

Kit includes heat gun, shrink and spreader attachments with storage case

ORDERING INFORMATION

Model No.	Description
PH-2100	Proheat Heat Gun 230V, 50/60Hz, 6.2A
PH-2100K	Proheat Kit includes heat gun, attachments (35017, 35016) and storage case

TECHNICAL SPECIFICATIONS: PH-2100, PH-2100K

Voltage: 230V, 50Hz, 6.2A

Output: 1410W maximum

Temperature: 221°C or 449°C

Airflow Volume: 425 l/min.

Motor: Permanent magnet

Nozzle Opening: 22.1cm diameter

Cordset: 1.82m, 3-wire grounded

Dimensions: 20.8cm L x 7.6cm W x 25.5cm H

Net Weight Gun Only: 0.737kg

Shipping Weight PH-2100: 1.36kg

Shipping Weight PH-2100K: 3.18kg

U.S. Patent No. 334.876

Proheat Attachments and Accessories

Professional quality attachments and accessories add versatility to your Proheat Heat Guns.

These nozzle attachments direct, concentrate or reflect heat to allow more versatile and precise applications for your heat tool. Expand your capabilities, improve job quality and save time using Master Attachments and Accessories.



Nozzle Shield
Prevents nozzle contact
Part No. 35026



Bench Stand
To position heat guns for various applications
Part No. 35216



Storage Case
Transport and storage in a rugged plastic carrying case
Part No. 35351



34.9mm Shrink Attachment
Shrink tubing
Part No. 35017



88.9mm Spreader Attachment
Spread air over large area
Part No. 35016



12.7mm Specialty Connector Attachment
Terminate tubing and specialty connectors
Part No. 35292*



7.9mm Pinpoint Attachment
Pinpoint hot air source for desoldering and welding PVC
Part No. 35294*



14.3mm Reducer Attachment
Direct hot air source for desoldering and welding PVC
Part No. 35293*




Get all 5!
Attachment Kit
Five attachments
Part No. 35309

Professional Quality Heat Guns. Perfect for many jobs.



Activate Adhesives



Solder Copper Pipe



Dry/Seal Insulation



Shrink Tubing



Weld Roofing Felt




Bend Plastics and PVC



Remove Decals



Shrink Package




Strip Paint



Loosen Bolts



Terminate Specialty Connectors



Desolder



Designers and Manufacturers of Heat Tools for Industry

FOR MASTER PRODUCTS CONTACT:

*Not for use with Model PH-2100.

As with all electrical equipment and tools, for your safety, read the instruction manual before using.

All information including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of this product for their application. The only obligations of Master Appliance are those in the Standard Terms and Conditions of Sale for this product. In no case will Master Appliance be liable for any incidental indirect, or consequential damages arising from the sale, resale, use or misuse of this product.

Master Appliance Corp. • 2420 18th St. • Racine, WI 53403 USA • Phone 01-262-633-7791 • Fax 01-262-633-9745

Web Site: www.masterappliance.com E-mail: sales@masterappliance.com

FORM# 58340